

# **SCH**

**(SUPPLIES) LIMITED**

**Manufacturers & Suppliers of Estate & Garden Machinery**  
**TELEPHONE 01473 328272 • FAX 01473 327177**  
**[www.schsupplies.co.uk](http://www.schsupplies.co.uk)**

## **OPERATING INSTRUCTIONS**



## **LARGE CAPACITY TRAILED COLLECTOR**

**Ref: TRCL**

## SAFETY

This large capacity trailer has been developed by SCH to tow behind tractors having the description known as 'twin cut'.

These tractors have a centre rear discharge blowing the cut grass/leaves into a limited size collection hopper. Frequent emptying is extremely time-consuming and frustrating.

The TRCL greatly increases the collecting capacity and therefore larger areas are collected in one fill, quicker, time saving and a great cost saving in labour.

The powerful motorised fan unit mounted on the front of the TRCL sucks up the green waste from the cutter deck and propels it into the trailer. The trailer has a low centre of gravity, which makes it extremely stable on hilly ground. Wide profile pneumatic wheels greatly reduce wheel markings on soft ground. The fan on the unit is belt driven to protect the engine should a blockage occur.

The units 'wandering hose' is ideal for use when dismantled from the towing vehicle.

## SPECIFICATIONS

Overall width	1168mm (46")
Overall length	2794mm (110")
Height	1442mm (56")
Weight	162kg
Blow diameter	530mm (21")
Engine	Honda 5.5hp manual start
Suction/delivery hose	200mm (8")

## SAFETY INSTRUCTIONS

A safety cut out switch is mounted on the fan casing. The engine will not start with the door open. The door must be securely closed before attempting to start.

- Ensure the trailer is securely attached to the towing vehicle.
- Ensure the hoses are in place and securely fixed.
- Ensure the fan front swing door is securely fixed.
- Never attempt to adjust, remove guards or clear blockages whilst the engine is running.
- The unit is designed to 'pick up' vegetable matter, Mineral and iron objects must be avoided.
- Never disconnect the suction hose from the blower.
- Never insert arms into the inlet or outlet orifices while the engine is running.
- Never point the discharge hose at any person.
- Should the discharge hose become damaged it must be replaced.
- Read and follow all safety instructions given in the engine manual.
- Be aware that the engine and exhaust will become hot when in use.

If in doubt, please call the SCH customer help line at **01473 328272**.

## TO PREPARE

1. Pull the cord at the front of the collector and 'tie off' when light.
2. Lay the web strap along the base of the trailer.
3. The remainder of the strap, take back to the rear top and secure, close doors and fix netting cover in place.

## OPERATION ADVICE

- Always travel at a low forward speed.
- If you hear the engine revolutions go down, stop collecting and let the revolutions build back up.

## TO EMPTY

1. Unclip the rear netting and open the two swing doors
2. Detach the top strap and pull. The wedge of collected leaves will pull out (a few will be left behind, simply rake these out).

## INTERNAL & FAN BLOCKAGES

1. Switch off tractor engine.
2. Switch off the fan engine.
3. Remove the connection hose.
4. Undo the retaining net on the doors.
5. Swing open the doors and clear the blockage.

## HOSE BLOCKAGES

If the long wander hose blocks, straighten the hose and create a 'wave' motion with the fan running.

## WARRANTY

Your unit is guaranteed for 12 months from date of purchase. This guarantee covers faults which may occur from defective parts or manufacture.



If you are missing your free brochure contact us on **01473 328272**, email **sales@schsupsplies.co.uk**, or visit our website **www.schsupsplies.co.uk**

