



Manufacturers & Suppliers of Estate & Garden Machinery
TELEPHONE 01473 328272 • FAX 01473 327177
www.schsupplies.co.uk

OPERATING INSTRUCTIONS



THE TRIANGLE BRUSH

Ref: TMB2

DESCRIPTION

The Triangular Brush gives the artificial play areas that vital 'scratch' in between major services. The wheels on the upper side of the brush make it an easy task to transport it to the storage area. Simply turn the brush onto the wheels.

SPECIFICATIONS

Working Width	1500mm (60")
---------------	--------------

SAFETY INSTRUCTIONS

- Never leave the brush on or around the playing areas. Always remove it to a place of safety before activities commence.
- On small to medium sized areas, only the towing vehicle operator should be present.
- Always store the unit in the transport position or standing up against a solid surface.
- Always make sure the unit is securely connected to the towing vehicle before use.
- Never travel at excessive speeds.
- Never allow any person to travel on the brush.

If in doubt, please call the SCH customer help line at **01473 328272**.

IMPORTANT

The SCH triangle brush should be only used in conjunction with the surface manufactures recommendations when used on an artificial surface.

GENERAL

The surface should have any unwanted debris removed before sweeping. (The tray on the sweeper is useful for debris collection)

The purpose of brushing at regular intervals, when conditions allow, will help to keep the infill mobile and the pile de-compacted.

Never tow the brush in the working position on any surface other than the surface it was intended for.

OPERATION

1. The brush is transported to the working area upside down and connected to the towing vehicle with the rigid tow bar.
2. At the brushing area, disconnect the brush from the towing vehicle and turn it onto its brushes
3. Re-connect the brush to the towing vehicle using the connecting chain.
4. Commence brushing. Never travel at such a speed that allows the brush to 'bounce'. The wandering action of the chain connection allows the brush to swing gently from side to side.

MAINTENANCE

- Should the brushes become soiled, wash with water (pressure wash if available).
- Check all fixings for tightness twice a year.

PARTS LIST FOR TMB2

Description	Quantity
Brushes & fixings	6
Transport wheels	2
Tow chain	1
Ball hitch for towing (optional)	1
Clevis hitch for towing	1

Please contact us for help with spare parts.

WARRANTY

Your unit is guaranteed for 12 months from date of purchase. This guarantee covers faults which may occur from defective parts or manufacture.



If you are missing your free brochure contact us on **01473 328272**, email **sales@schsupplies.co.uk**, or visit our website **www.schsupplies.co.uk**

