

SCH

(SUPPLIES) LIMITED

Manufacturers & Suppliers of Estate & Garden Machinery
TELEPHONE 01473 328272 • FAX 01473 327177
www.schsupplies.co.uk

OPERATING INSTRUCTIONS

MUST BE READ PRIOR TO OPERATING THIS MACHINE



Artificial Surface Grooming Rake

Ref: ASR2 / 3ASR2

ROLLER / TOOL CARRIER - BRT

The artificial surface grooming rake is a small but effective machine to carry out routine maintenance on artificial playing surfaces with a sand base. The two rows of staggered spring tines tease through the playing surface to remove any surface compaction and aid drainage.

A weight tray is incorporated into the design so that top weight may be added to aid penetration on heavily compacted surfaces. The trailing brush will level and groom the play area; having completed the operation the play area will be in a ready state for many hours of hard use.

Each working row of tines may be lifted out of work individually to suit your grooming requirements, i.e. lift out of work the two spring tine rows and leave the brush in work.

This Simple grooming unit may be towed behind 13 hp tractors and above.

SPECIFICATIONS

Working Width - ASR2	1200mm (48")
Working Width – 3ASR2	1500mm (60")

Towed version – ASR2

Three-point linkage mounted version – 3ASR2

SAFETY INSTRUCTIONS

- Never leave your grooming rake where someone could trip or walk into it.
- Always make sure that the rake is firmly fixed to the towing vehicle when in use.
- Never allow people to ride on the frame.
- Be aware of your surroundings and do not use the rake in close proximity to other people.
- Do not travel at speeds which would allow the unit to bounce.
- Do not turn sharply at the end of a row, take a wide turning arc.
- Never reverse the unit with the tines or brush in contact with the ground.

If in doubt, please call the SCH customer help line at 01473 328272.

OPERATION

The ASR2 unit has a steel cable which can be used to raise the tines from the ground. This cable can be attached to the cleat on the tow bar to secure it whilst travelling to and from the storage area. Make sure the two rakes and brush bar are in the 'up' position.

For use:

1. For rakes only (make sure the transport cable is released). Lower the rakes into the working position. Pull out the spring-loaded catch, holding the correct position, allow the spring bolt to return to secure the rake
2. To use the brush - lower as for the rakes.
3. To use only the brush – raise the two rows of rakes.
4. The incorporated weight tray can hold 25kg (55lbs) of top weight.

WARRANTY

Your Artificial Surface Grooming Rake is guaranteed for 12 months from the date of purchase. This guarantee covers faults which may occur from defective parts or manufacture.

Damage caused by inability to follow instructions will void warranty.



If you are missing your free brochure contact us on **01473 328272**, email **sales@schsupplies.co.uk**, or visit our website **www.schsupplies.co.uk**

